



OPERATING INSTRUCTIONS BOOKLET N.º 6400GBBL

EKMAN HIGH VISIBILITY VEST

Type N.º L140HV-L160HV

Type N.º L149 with the
extension "O" for orange HV fabric
or "Y" for yellow HV fabric



FITTING AND ADJUSTMENT OF HIGH VISIBILITY VEST L140HV-L160HV

- 1- Fit vest over shoulders as a normal jacket.
 - 2- Close zip.
 - 3- When standing upright, the vest should be comfortable, without undue pressure on chest shoulders.
 - 4- An toolholder or boltbag is available and could be fitted to any preferred side.
- For L149 "O" or L149 "Y" see supplied user instruction booklet.

WARNING:

Only follow the directions in the En471 Class 1 for this high visibility vest, do not use for a application requiring a higher performance of high visibility.

LIMITATIONS OF USE:

This high visibility vest is in conformity with the provisions of Council Directive 89/686/EEC, and the European standard En471 Class 1 and should therefore only be used as stipulated in those provisions. It is recommended that the high visibility vest should be used as a personal issue, but if in multiple use, each user should follow manufacturer's instructions for use, inspections etc. promptly in the same way as a personal issue.

PACKING AND STORING INSTRUCTIONS:

For transporting the vest should be packed in a textile carrying bag of suitable size and not together with any sharp edged tools etc. The vest must be returned to the store when not in use and should should not be left lying around the site/works. The vest should not be packed or stored with sharply edged tools, soldering irons or acids. Keep in a cool dry place, away from direct sunlight. Do not store near radiators, stoves, steam pipes or places where the fabric and the stripes would be subject to excessive heat or dampness.

MARKING:

The high visibility warning clothing is grouped into three classes(1,2,3) whereby class 3 is the highest level of visibility. The product label is marked X=1 which means class 1 and a visible background material of minima 0.14m² and retroreflective material of minima 0.10m². The retroreflective tape is grouped into two classes (1,2) whereby class 2 is the highest level of retroreflection. The product label is marked Y=2 which means class 2 of retroreflections of the tape

WASHING INSTRUCTIONS:

Light soiling on fabrics can be removed with a damp sponge. More ingrained dirt can be removed with soap or mild detergent. Avoid getting soap into the adjustment buckles. Rinse with clean water, remove surplus moisture with a cloth and allow to dry naturally away from any direct source of heat. Heavy deposits of creosote or grease may be removed with a diluted solution of heavy detergent and water. The diluted liquid should be worked into the fabric with a brush then rinsed off with clean water. Wipe as dry as possible and allow to dry naturally away from any direct source of heat. For machine wash see label on the product. Maximum number of cleaning processes for machine wash 25.

MANUFACTURER:

Fallsafe Online Lda.
Zona Industrial das Pateiras
Lote 22
S. Tiago de Bougado
4785-623 Trofa
Portugal



Quality management system of Fallsafe Online Lda is assessed and registered as meeting the requirements of ISO9001:2000
Notified Body N.º 0120, Certificate N.º Q/2581